



Magnifica potenza di un diffusore a tre vie da pavimento: fine timbrica, componentistica allo stato dell'arte e finiture di pregio. Interprete assoluto della migliore tradizione *Sonus faber*.

Magnificent power of a three-way floor-standing loudspeaker: tonal fineness, state-of-the-art components and valuable finishes. Absolute interpreter of Sonus faber tradition.

SYSTEM	3 way floorstanding vented box loudspeaker.
CABINET	Lute shape design, ensures excellent stiffness for resonances and standing waves control.
TWEETER	Ultra dynamic linearity driver, 25 mm ring radiator, magnetically shielded.
MIDRANGE	150 mm cone driver with Symmetric Drive Motor System and selected hard paper "sliced" cone for high resolution and total break-up control. Dynamic linear suspension.
WOOFERS	180 mm cone driver with Symmetric Drive Motor System and selected hard paper "sliced" cone for high resolution and total break-up control.
CROSS-OVER	Non-resonant acoustic first order design, optimized for acoustic phase response.
FREQUENCY RESPONSE	32 Hz - 40.000 Hz, tuning ports included.
SENSITIVITY	90 db SPL (2.83 V/1m).
NOMINAL IMPEDANCE	4 ohms.
POWER HANDLING:	50W - 300W, without clipping.
FINISH	32 pieces of solid and laminated maple wood, finished in a multicoating of medium gloss ecologically sensitive lacquer. Natural or light graphite.
DIMENSIONS	225 x 430 x 1090 mm (WxDxH).
WEIGHT	68 Kg per pair - net weight/72 Kg per pair - shipping weight.