Sonus faber

WALL DOMUS





Diffusore compatto studiato per impiego in ambiente home theatre. Le forme particolari e la staffa regolabile in dotazione consentono di tararne sia il posizionamento che l'orientamento, così da incontrare le più diverse necessità di installazione.

A compact sound diffuser designed for use in home theatre environments. The special shapes and the adjustable bracket supplied make it possible to calibrate its position and direction, thus ensuring even the most diverse installation requirements are complied with.

SYSTEM 2 way loudspeaker, front reflex port.

CABINETConstruction with de-coupled side panels for resonances control.

TWEETER Custom design, ultra dynamic linearity driver, 19 mm ring radiator, magnetically shielded.

MID-WOOFER Custom design, free compression driver, 150 mm paper coated cone, magnetically shielded.

CROSS-OVER Ideal blending, initial first order, distributed multi - slope,

optimized phase characteristics for correct space/time performance, cross point 3600 Hz.

FREQUENCY RESPONSE 55 Hz – 20.000 Hz, tuning port included.

SENSITIVITY 88 db SPL (2.83V/1m).

NOMINAL IMPEDANCE 4 ohms.

POWER HANDLING 30W - 150W, without clipping.

FINISH Combination of black leather and teak or black piano lacquer.

DIMENSIONS 185 x 180 x 480 mm (WxDxH).

WEIGHT 11 Kg per pair - net weight/14 Kg per pair - shipping weight.