


cremona M



SYSTEM: 3 way floorstanding vented box loudspeaker.

CABINET: Lute shape design, combination of sandwich construction, obtained using 20 hand selected wood layers and solid maple, quality graded and oriented for carefully optimized resonances control. Sub-structural ribs are strategically placed for absolute rejection of spurious vibration and standing waves control.

TWEETER: 25 mm ultra dynamic ring radiator-driver.

MIDRANGE: 150 mm cone driver with Symmetric Drive Motor System and selected black wood fiber cone, high resolution, treated for break-up control. Dynamic linear suspension. Designed synergistically with its vented acoustic chamber. Sonus faber exclusive.

WOOFERS: 180 mm lightweight Aluminum/Magnesium alloy cone drivers. Ultra dynamic performance and linearity. Special coaxial anti-compressors are used, designed to remove cavity resonance and distortions.

CROSS-OVER: Non-resonant second order design, optimized phase characteristics for optimal space/time performance, cross-over points 400Hz – 2300Hz

FREQUENCY RESPONSE: 40 Hz – 30.000 Hz, tuning ports included.

SENSITIVITY: 91 dB SPL (2.83 V/1m).

NOMINAL IMPEDANCE: 4 ohms.

POWER HANDLING: 50W – 250W, without clipping.

FINISH: Natural maple multicoated with medium gloss ecologically sensitive lacquer.

DIMENSIONS: 350 x 565 x 1120 mm (WxDxH).

WEIGHT: 73 Kg per pair – net weight/ 87.5 Kg per pair – shipping weight.