



MICROMEGA

PA20

The PA-20 Preamplifier

The new PA-20 preamplifier, together with the PW-250 and the PW-400, its power partners, are capable of reaching levels of reproduction which are unattainable with an integrated solution.

The PA-20 shares some of its functionalities with the IA-60, IA-100 and IA-180, the three integrated amplifiers of this range. This particular range was designed to be ergonomically intuitive and the interface easy to use, thus enabling smooth transition when switching from one model to another.

It also features the MICROMEGA ACTS® power supply which allows the PA-20 to reproduce the most complex musical signals in a totally effortless manner, with a great sense of dynamic.

Technical characteristics

Line level inputs	5
Line level input sensitivity	280 mV
Line level input impedance	47 kΩ
MM phono input	1
Phono input sensitivity	5 mV
Phono input impedance	47 kΩ
Processor input	1
Sub Input	1
2.1 Mode	Yes
Tape out output impedance	600 Ω
Headphone output power	2 W
Minimum headphone impedance	32 Ω
Line Output impedance (1 kHz)	600 Ω
Bandwidth (- 3 dB)	10 Hz - 100 kHz
THD + noise (20 Hz-20 kHz)	< 0.02%
Maximum power consumption	50 W
Dimensions (W x D x H mm)	430 x 300 x 70 mm
Weight	6.0 kg

AUDIS SARL, 13-15 rue du 8 mai 1945 - 94470 Boissy Saint Léger - FRANCE

Tel: 01 43 82 88 60 Fax: 01 43 82 61 29 E-mail: info@micromega-hifi.com Internet: www.micromega-hifi.com

Audis SARL has the right to modify the technical and performance characteristics of its audio-video products without prior notification.