

DreamVision®

	DreamWeaver <i>Plus</i>	DreamWeaver Two
Projection system	TI Mustang HD2+ LVDS 12° DMD	TI Matterhorn LVDS 12° DMD
Carl Zeiss Projection Lens	Carl Zeiss Projection Lens: F/1.9,26.7 - 36.8mm focal length	Carl Zeiss Projection Lens: F/1.9,26.7 - 36.8mm focal length
Color Wheel	7 segments (RGBRGBG), 5 x (9000rps, 300Hz, 6500K color temperature)	6 segments (RGBRGB), 5 x (9000rps, 300Hz, 6500K color temperature)
Resolution	1280 x 720 16:9	1024 x 576 16:9
Contrast Ratio	2300:1 full on / full off	1500:1 full on / full off
Lamp	220 Watt UHP (3000 hours life time)	220 Watt UHP (3000 hours life time)
Brightness	1200 lumens	1100 lumens
Colors	16.7 millions simultaneously display able	16.7 millions simultaneously display able
Installation	Front, Rear, Table, Ceiling (Ceiling bracket in option)	Front, Rear, Table, Ceiling (Ceiling bracket in option)
Keystone Correction	Digital up to +/- 20° Vertical, +/- 9° Horizontal	Digital up to +/- 20°
Inputs	2 x components - gold RCA 1 x Component - 15-pin D Sub 2 x S-VHS - Mini Din 4-pin 1 x Composite Video - RCA 1 x DVI - M1-DA VESA 1 x HDTV Analog - 15-pin D Sub 1 x RS232 control - 9-pin D Sub 1 x IR Repeater (Niles / Xantech compatible) - 3.5 mm mini-jack 2 x 12 V trigger - 3.5 mm mini-jack 1 x USB 1 x Power supply	2 x components - gold RCA 1 x Component - 15-pin D Sub 2 x S-VHS - Mini Din 4-pin 1 x Composite Video - RCA 1 x DVI - M1-DA VESA 1 x HDTV Analog - 15-pin D Sub 1 x RS232 control - 9-pin D Sub 1 x IR Repeater (Niles / Xantech compatible) - 3.5 mm mini-jack 2 x 12 V trigger - 3.5 mm mini-jack 1 x USB 1 x Power supply
Video Compatibility	Component and RGB HDTV (720p, 1035i, 1080i, 1080p, 1080p-24Hz) Component EDTV (480p, 576p progressive scan), SECAM: M, Component, composite and S-Video standard video. (480i, 576i, 576i RGB SCART with adapter, NTSC, NTSC M 4.43, PAL: B, G, H, I, M, N)	Component and RGB HDTV (720p, 1035i, 1080i, 1080p, 1080p-24Hz) Component EDTV (480p, 576p progressive scan), SECAM: M, Component, composite and S-Video standard video. (480i, 576i, 576i RGB SCART with adapter, NTSC, NTSC M 4.43, PAL: B, G, H, I, M, N)
Size	Ø439 mm - High 127 mm	Ø439 mm - High 127 mm
Weigh	4.4 Kg	4.4 Kg
Audible Noise	25 dB	27 dB
Remote Control	Premium backlight learning remote control	Standard fully functioned remote control



DreamWeaver+ projection distances

Screen Width	Short Throw	Long Throw
150 cm / 59.06"	223,88 cm / 88.14"	312,50 cm / 123.03"
180 cm / 70.87"	268,66 cm / 105.77"	375,00 cm / 147.64"
200 cm / 78.74"	298,51 cm / 117.52"	416,67 cm / 164.04"
250 cm / 98.42"	373,13 cm / 146.90"	520,83 cm / 205.05"
300 cm / 118.11"	447,76 cm / 176.28"	625,00 cm / 246.06"

DreamWeaver Two projection distances

Screen Width	Short Throw	Long Throw
150 cm / 59.06"	279,85 cm / 110.18"	390,63 cm / 153.79"
180 cm / 70.87"	335,82 cm / 132.21"	468,75 cm / 184.55"
200 cm / 78.74"	373,13 cm / 146.90"	520,83 cm / 205.05"
250 cm / 98.42"	466,42 cm / 183.63"	651,04 cm / 256.31"
300 cm / 118.11"	559,70 cm / 220.35"	781,25 cm / 307.58"

www.dreamvision.net

DreamVision
WE MAKE THE WORLD DREAM



LET'S DREAM

DreamWeaver *Plus*
DreamWeaver Two