
PASSION FOR SOUND OCTOBER 2006 E3.95 WWW.HIFICHOICE.CO.UK



Мз dual mono integrated amplifier CD VOL -31.0dB 0000000

IN-DEPTH TEST New flagship amp

and CD player



Arcam DV137 universal



ATC Studio sound from



Rotel Pre/power amp





FEATURING

- Cambridge 640C v2 Marantz SA7001 KI
- Creek Evo
- Denon-1500AE
- Rega Apollo Shanling CD-T80

Power of valves

Great build quality and a competitive price... but do these valve monoblocks deliver a sound to match?

PRODUCT PrimaLuna ProLogue Six

TYPE Valve monoblock power amplifier

PRICE £788 (£1,576 per pair)

KEY FEATURES Size (WxHxD): 28x19x39.5cm

O Weight: 19kg O Inputs: single RCA phono socket

O Rated power: 70 watts per channel into two, four or eight ohms O Signal ∕ noise ratio: 101dB (unweighted) at full rated power O Input impedance: 100k ohms

CONTACT № 020 8971 3909 @ www.primaluna.nl

he ProLogue Six is the latest in an expanding range of valve amplifiers based on a common circuit architecture and external design. It's available in two versions, with either KT88 or EL34 output valves. The KT88-equipped model (not tested here) commands a £200 premium.

Although the brand was only recently established (in 2003), the three individuals behind PrimaLuna have been involved in high-end audio for a long time in retail, service and design. The company is of Dutch origin

but Chinese manufacture helps keep prices in check, and value for money is written all over the PrimaLuna range in big letters.

If any valve amplifier was designed for the first-time valve user, this is it. The design is fundamentally simple (although there are some novel tweaks), with a phase splitter and driver stage. Rated at 70 watts, each monoblock includes a complement of two 12AX7 dual triodes and two 12AU7s in addition to the four EL34s. The output valves work in an enhanced Ultralinear Class AB mode, which is presented as offering performance and power output somewhere between conventional pentode mode and pure Class A. There is no black magic here - just choose the appropriate output tap (two, four or eight ohms), connect your input to the single phono socket and you're ready to rock.

In common with other PrimaLuna designs, the ProLogue Six goes all out for practicality, particularly with Adaptive AutoBias, which constantly adjusts bias levels in the output stage according to circuit conditions. This is the only major part of the circuit that is produced on a board, rather than hard-wired. Adaptive AutoBias eliminates the need for manual biasing of the output valves, and is claimed to reduce distortion, increase valve life, and eliminate the need for matched valves in the output stage. It is also said to eliminate the need for conventional negative feedback, but if this means that the amplifier has a higher than normal output impedance, the amplifier will be load sensitive. This is because its output impedance will interact with the reactive component of the loudspeaker impedance, with the possibility of unpredictable sonic balances when switching between speakers. Some of the listening tests (see below) were designed to assess whether such effects would be audible.

It would be remiss not to acknowledge build quality, which at the price is exceptional, both in terms of finish, general solidity and even such thoughtful details as the cleverly







"It has a smooth, easy-on-the-ear style, with a warmish and slightly loose balance - a quintessentially 'valve' type of sound."

decoupled valve cage cover. Internal highlights include a heavy power supply and hardwired construction. The only user control is the power switch, which is awkwardly positioned on the left hand side of the unit. The socketry all looks like WBT-sourced components, though they may be pattern parts.

SOUND QUALITY

Different speaker designs expose changes in system voicing, due to the high output impedance. During our test, for example, Mordaunt-Short's Performance Six sounded light in balance through the midband and upper bass, while Monitor Audio's GS10 was significantly sharper and more substantial.

But there are common factors, too. The amp has a smooth, easy-on-the-ear style, with a warmish and slightly loose balance - a quintessentially 'valve' type of sound. In every system combination tested, there was a lack of articulation and separation. There is no real shortage of detail, but the overall effect was as though listening to the music through a very

> faint fog. Nor is there a global lack of dynamics, despite some smudging of the subtle differences that separate out members of an instrumental group. In its favour, the amp sounds fluid and easy going, and is electrically quiet, with no obvious indications of microphony.

But ultimately there is not enough excitement, either. It's a clean and presentable sounding amplifier, and an engaging one in its own way. Power output is impressive, though the amplifier can become shrill in the midrange and treble when played at too high a volume (not a traditional valve characteristic). What it doesn't do musically, however, is to explore the depths and complexities of really fine recordings, represented for much of this test with large-scale orchestral and small-scale female vocal material. Ultimately it doesn't really make music sing.

This is a highly interesting design, which has many features to its credit, especially when it comes to price and build. It also has certain qualities that will not endear it to some. HFC

Alvin Gold





VERDICT SOUND >> 81% PRO Simple and purposeful design that features a powerful auto-adjusting output stage and fine build quality. FEATURES >> 65% M CON Evidence of load sensitivity BUILD>> 92%

means loudspeaker matching must be made with exceptional care and attention. Sound lacks the separation and articulation of the best in class.

eat material value for a valve monoblock, but it invites the

PROLOGUE THREE PREAMPLIFIER

The obvious partner for the ProLogue Six monoblocks is PrimaLuna's matching ProLogue Three preamplifier (£1,099). It's housed in the same narrow format casing, and is a similarly 'keep it simple' design. Facilities are limited to four identical line-level inputs, a single tape output pair and two pairs of preamp level outputs, all single-ended, and with control limited to the smooth as silk ALPS analogue volume control

There is no balance control, no remote control and no global feedback, despite which the amplifier is said to offer a low and constant output impedance without the need for a cathode follower output. An internal MM phono stage is available as an extra cost option. The valve complement includes two 12AX7,